

AFRITOOL (M) LDA.

Av. 25 de Setembro No. 2009 Caixa Postal N°2183, Maputo Moçambique Tel: +258 21 309 068/328 998 Fax: +258 21 328 997/333 809 e-mail: afritool@tvcabo.co.mz / afritool@afritool.com Nuit: 400109524

Specifications Generator EM 10000	
Type	R
Generator	
AC frequency	-
AC output voltage	-
Rated AC output	8000 VA
Maximum AC output	9000 VA
DC output	-
Voltage regulation system	AVR
Engine	
Model	GX620K1
Туре	Air Cooled, 4-stroke OHV 900, V-Twin
Displacement	614 cm3
Net Power (SAE J1349)*	13.5kW (18.1 HP)/3600 min-1 rpm
Rated power output	11.8.0kW (15.8 HP)/3600 min-1 rpm
Max. Net Torque (SAE J1349)*	40.5 N.m (4.14 kgf.m, 29.9 lbf.ft)/2500 min-1
Fuel tank capacity	31 L
Fuel used	Unleaded gasoline (Oktan 86 or higher)
Ignition system	Transistorized Magneto
Starting system	Electric starter
Continuous operating hour	-
Operating noise level (7m)	-
(Lwa)	101 dB
Air cleaner	Dry paper type
Oil capacity	Without oil filter repalcement : 1.1 L
	With oil filter repalcement : 1.4 L
Recommended oil	-
Dimensions	
Length	973 mm
Width	552 mm
Height	637 mm
Dry weight (kg)	150 kg
Standard Features	
Eco-Throttle	-
AC circuit breaker	V
DC circuit breaker	-
Oil alert	v
Fuel indicator	v
Voltmeter	v
Parallel operation connection port	-
Parallel operation connection cable	-











AFRITOOL (M) LDA. I

Av. 25 de Setembro No. 2009 Caixa Postal N°2183, Maputo Moçambique Tel: +258 21 309 068/328 998 Fax: +258 21 328 997/333 809 e-mail: afritool@tvcabo.co.mz / afritool@afritool.com Nuit: 400109524

i-monitor	-
Remote Control Box	-
Large capacity air cleaner	-
Large capacity fuel tank	-
Large capacity muffler	-
*With eco throttle switch on.	

Product Features

Honda 4-Stroke engine, OHV, 90° V-Twin, 2 Cylinder GX620
Rated Output 800VA / Max. Output 9000VA
Net Weight 150Kg
With automatic Voltage Regulator (AVR)
Electric starter Sysytem for easier starting
Quite operation73dB(A), during 8000 - 9000 W
operation







