ST1300 SuperTourer

HONDA The Power of Dreams

The high-performance ST1300 moves the continental touring experience to unprecedented levels of seamless comfort and exacting control.



SPECIFICATIONS:

Engine:

1261cc liquid-cooled longitudinally mounted 90-degree V-4 Type:

Bore and Stroke: 78.0mm x 66.0mm

Compression Ratio: 10.8:1

Valve Train: DOHC; four valves per cylinder

Fuel System:

Carburetion: Programmed Fuel Injection (PGM-FI) with automatic

enricher circuit 29.1 litres

Fuel Capacity: Electrical:

Ignition: Computer-controlled digital with three-dimensional

mapping and electronic advance

Drivetrain:

Transmission: Five-speed Final Drive: Shaft

Suspension:

45mm HMAS cartridge fork; 116mm travel Rear: HMAS gas-charged single shock with five-

position spring-preload adjustability; 122mm travel

Brakes:

Front:

Dual full-floating 310mm discs with Front:

LBS three-piston calipers

Rear: Single 316mm disc with LBS three-piston caliper

Tyres:

Front: 120/70ZR-18 170/60ZR-17

Chassis:

26°

Rake: Trail: 98.0mm Wheelbase 1,490mm Seat Height 789mm

Dry Weight: 283ka

All specifications are provisional and subject to change without notice.





HONDA SOUTH AFRICA (PTY) Ltd. A wholly owned subsidiary of Honda Motor Company Japan.